



# ALL-PRO HP

ALTERNATIVE SOLUTION

# ALL-PRO HP

ALTERNATIVE SOLUTION

## CBX, the strong performer

**NEXEN ALL-PRO HP** designed by tires specialists  
**New standard of solid tires** with reasonable prices  
 and great performance



SIZE		Easy-Fit	O.D.	W.D.	Load Capacity(KG)	
TIRE	RIM	CLICK	mm	mm	Load	Steer
5.00 - 8	3.00D	O	458	125	1415	1090
15 X 4 1/2 - 8 (125 / 75 - 8)	3.00D	O	376	115	1040	800
16 X 6 - 8 (150 / 75 - 8)	4.33RW	O	419	152	1495	1150
18 X 7 - 8 (180 / 70 - 8)	4.33RW	O	454	156	2145	1650
15 X 5 1/2 - 9 (140 / 55 - 9)	4.00E	O	384	131	1170	900
6.00 - 9	4.00E	O	530	139	1885	1450
21 X 8 - 9 (200 / 75 - 9)	6.00E	O	518	184	2755	2120
200 / 50 - 10	6.50F	O	457	198	2470	1900
6.50 - 10	5.00F	O	580	172	2340	1800
23 X 9 - 10 (225 / 75 - 10)	6.50E	O	583	204	3445	2650
7.00 - 12	5.00S	O	653	172	2920	2240
23 X 10 - 12 (250 / 60 - 12)	8.00G	O	589	240	3770	2900
27 X 10 - 12 (250 / 75 - 12)	8.00G	O	676	246	3900	3000
8.15 - 15 (28 X 9 - 15, 225 / 75 - 15)	7.00	O	696	212	3445	2650
28 X 12.5 - 15 (355 / 45 - 15)	9.75	O	711	310	5525	4250
32 X 12.1 - 15	9.75	O	807	299	6500	5000
355 / 65 - 15	9.75	O	822	300	7800	6000
250 - 15 (205 / 70 - 15)	7.00	O	716	226	4745	3650
250 - 15 (205 / 70 - 15)	7.50	O	716	226	4745	3650
300 - 15 (315 / 70 - 15)	8.00	O	812	266	5850	4500
7.00 - 15	5.50	O	734	175	3545	2725
7.50 - 15	6.50	O	755	197	3900	3000
8.25 - 15	6.50	O	814	202	4750	3650

\* Load capacity : Counter Balanced Forklift Truck, up to 25 km/h

**NEXEN** NEXEN CORPORATION

5F NEXEN Gangnam Tower, 226, Bangbae-ro  
 Seocho-gu, Seoul, KOREA 06584  
 solidtire@nexentire.com

www.nexensolidtire.com