



KENEX

BRANDED BY NEXEN

 NEXEN CORPORATION

KENEX

BRANDED BY NEXEN

New standard guaranteed by NEXEN, **KENEX**



Tire Size			O.D. mm	W.D. mm	Load Capacity(kg)				Inflation Pressure		
Size	PR	Rim			*Forklift		Other Vehicles		kPa	psi	
					Front	Rear	10km/h	25km/h			
8"	5.00-8	10	3.50D	470	137	1,150	970	-	-	1,000	145
	16X6-8	16	4.33R	425	152	1,495	1,150	1,495	1,150	1,000	145
	18X7-8	16	4.33R	465	173	1,695	1,450	1,450	1,055	1,000	145
9"	6.00-9	12	4.00E	540	160	1,675	1,415	1,415	1,045	1,030	149
	21X8-9	16	6.00E	535	200	2,755	2,120	2,755	2,120	1,000	145
10"	6.50-10	12	5.00F	590	175	1,895	1,600	-	-	1,000	145
12"	7.00-12	14	5.00S	676	190	2,590	2,190	2,190	1,610	1,000	145
15"	7.00-15	14	5.5	750	200	3,140	2,655	2,655	1,955	1,000	145
	7.50-15	16	6.0	780	215	3,550	2,980	2,975	2,190	1,000	145
	8.15-15 (28X9-15)	16	7.0	710	220	3,115	2,630	2,630	1,940	1,000	145
	8.25-15	16	6.5	840	235	4,050	3,450	3,450	2,520	925	134
	250-15	18	7.5	735	250	4,110	3,470	3,470	2,555	1,030	149
	300-15	20	8.0	840	300	5,940	4,990	4,990	3,675	930	135
16"	7.50-16	12	6.00G	805	215	3,195	2,700	2,700	1,990	790	115

* Load capacity is based on counter balanced forklift truck and guaranteed up to 25km/h.

 **NEXEN CORPORATION**

177, Magokjungang-ro, Gangseo-gu,
Seoul, Korea 07594

solidtire@nexentire.com

www.nexensolidtire.com

